

MU-M600

Rear mounting, hydraulic folding
up to 250 HP, 600 cm WW



Standard Equipment

- Manufactured from High Quality QSt/E Steel with Headstock Cat.II + III for Rear mounting.
- 4 rubber wheels , 360° swivel, height adjustable, 23X10.50-12,
- Gearbox with integrated over run clutch for 1000 r.p.m
- Automatic belt tensioning
- Hood wear plates
- Hydraulic transport safety lock at an angle of 90°
- High tempered "M" Hammer flails to ensure clean cut and maximum shredding using less power.
- Well balanced spiral Rotor with specially formed flail lugs to protect against damage from obstacles and internal bearings protecting against dirt, wear and tear.
- Patented removable shredding bar – System: "Shark fin".
- Carbide wearing skids, removeable
- High tempered one way spring steel protection flaps in front of the mower hood.
- Optimised distance between the outer rotor circle and the wheels guarantees perfect contour following and an even quality of cut.
- 2 single acting spool valves requested
- P.T.O. shaft with cap bottom lubrication.
- Warning signs and lights (LED mounted)

Options

- Second patented removable shredding bar – System: "Shark fin"
- Hydraulically driven mower for the middle between the hoods
Hydraulic required: 1x forerun, 1x free flow, 1x free flow leakage back to the oil tank (delivery time to be ask for)
- Working hours meter with electronic sensor.

Technical Data

Model	WW cm	Overall Width cm	Tractor HP	Weight kg	No. of flails
MU-M600	600	620	140-250	2500	52

D-59494 Soest
Am Silberg 23
Telefon +49 (0) 29 21 - 96 51-0
Telefax +49 (0) 29 21 - 7 30 80
soest@muething.com

D- 97215 Uffenheim
Am Brunnlein 2
Telefon +49 (0) 98 42 - 98 66-0
Telefax +49 (0) 98 42 - 98 66 67
uffenheim@muething.com



Muething
since 1898 - tradition to build the future